


7675-73

Steel wire ropes. Locked conveying wire rope with one layer of V-shaped wire, one layer of Z-wire and type TK cope. Dimensions 12 5100, 12 5200

01.01.75

1.

1+6+12 1+6+12+18.



2.

											, (), , / 2(/ 2)					
										100	1186 (120)	1270 (130)	1370 (140)	1470 (150)	1570 (160)	1670 (170)
38,5	3,3	19	5	17	17,8	6	18	30,6	1015,90	869,20	1190 (121500)	1290 (132000)	1390 (142000)	1485 (152000)	1590 (162500)	1690 (172500)
40,5	3,7	19	5	18	19,0	6	19	30,6	1127,69	964,81	1320 (135000)	1435 (146500)	1540 (157500)	1655 (169000)	1760 (180000)	1875 (191500)
42,5	4,1	19	5	19	19,0	6	20	30,6	1223,84	1046,84	1435 (146500)	1555 (159000)	1675 (171000)	1795 (183500)	1915 (195500)	2035 (208000)
45,0	4,0	19	5	20	19,6	6	21	31,0	1358,76	1162,01	1595 (163000)	1725 (176500)	1860 (190000)	1990 (203500)	2125 (217000)	2255 (23051)
47,0	3,6	37	5	22	19,0	6	22	31,0	1476,62	1262,58	1730 (177000)	1875 (191500)	2020 (206500)	2165 (221000)	2310 (236000)	2455 (251000)
51,0	4,1	37	5	24	19,6	6	24	31,0	1702,89	1455,70	1995 (204000)	2165 (221000)	2330 (238000)	2495 (255000)	2665 (272000)	2830 (289000)

82

104

1, (, . 2).

2,

3,

1370 / 2(140 / 2)

01,01,91,

45,0

1180 / 2(120 / 2):

Km 45,0- - -1

7675-73

(, , 1,2),

3. — , 18899. , , , , -

1.

2. — 15.06.73 1484

3. 7675-55

4. -

18899-73	3
----------	---

5. , — — (4-94) ⁴⁻⁹³ -

6. 1, 2, 1985 ., 1989 . (6-85, 3-90)